

Widely Distributed Modeling & Simulation in Aerospace & Defense Using the HLA standard

MODPROD, Linköping 2010-02-10

Björn Möller, Pitch Technologies AB



- » A few words about Pitch
- » Simulation Interoperability – What is the problem?
- » The HLA Standard
- » Model Based Engineering, Modeling and Simulation and Interoperability
- » Real world examples & challenges
- » Widely distributed Modeling & Simulation
- » Conclusions



Army



Navy



Air Force



PSO.



Space




Industry



Energy

- » World leader in standards-based interoperability products
- » Provides standards-based tools to more than 300 customer organizations in more than 30 countries
- » Strong focus on R&D and innovation
 - » Develops and delivers cutting-edge, industry-strength products
 - » International R&D leader with several research awards and certifications
- » Small, agile company with our own brand and an international partner network
- » Slogan: "Make Your Systems Work Together"
- » A BAE Systems company (head count: 100 000)



- » One necessary requirement to develop a serious simulation model is a high level of domain knowledge
 - » Different models are developed by different specialist companies, expert groups, researchers, etc
 - » Simulation models may be acquired from different sources together with the real systems (for example a real aircraft + simulator)
 - » The source may increase (or decrease) the credibility of the model
- » Different models come from different sources and were developed in different ways





- » To model "the bigger picture" we need to combine many different simulation models from different sources. Examples:
 - » Defense simulations: sensors, vehicles, weapons, effects, weather, tactical decision making, command and control...
 - » Environment simulations: chemical processes, ecology, meteorology, hydrology, human behavior...
 - » Offshore oil simulation: oil platforms, ships, drilling process, fluids, geology, people, ...
- » There is no single "correct" way to model a real world concept
- » Simulation Interoperability – making simulations work effectively together

- » Model
 - » A physical, mathematical or logical representation of a system, process or other phenomenon
- » Simulation
 - » Execution of a model over time
- » Distributed Simulation
 - » Synchronized execution of multiple models over time
 - » Models can be more or less distributed from using shared memory, LAN to WAN
- » High-Level Architecture (HLA), IEEE 1516-2010
 - » Open International Standard for Simulation Interoperability
- » Federation (HLA Terminology)
 - » A set of loosely coupled simulation systems, tools and infrastructure to support distributed simulation execution events


Interface to C2 Systems



Staff-Level Training / CAX







Computer Generated Forces



Interface to Live players & systems

Platform Trainers



Standard Information Data Exchange Services API (IEEE 1516)
Runtime Infrastructure (RTI)

Models can be executed in the same process or across the world
(with slightly different latency characteristics)


Category	Functionality
Federation Management	<ul style="list-style-type: none"> ◆ Create and delete federation executions ◆ Join and resign federation executions ◆ Control checkpoint, pause, resume, restart
Declaration Management	<ul style="list-style-type: none"> ◆ Establish intent to publish and subscribe to object attributes and interactions
Object Management	<ul style="list-style-type: none"> ◆ Create and delete object instances ◆ Distribute and control updates for attributes ◆ Distribute interactions
Ownership Management	<ul style="list-style-type: none"> ◆ Transfer ownership of objects/attributes
Time Management	<ul style="list-style-type: none"> ◆ Coordinate the advance of logical time and its relationship to real time
Data Distribution Management	<ul style="list-style-type: none"> ◆ Control the efficient routing of information between federates

Supports different types of time management (real-time, logical time, event driven, ...)

High performance: 100 000 updates/s, 0.2 ms latency

Scalable: tens or hundreds of simulator




Implementations for a plethora of operating systems & languages/compilers



The information exchange data model used by the RTI

Provided as an XML file – HLA can support any domain

Example above shown in UML style using a FOM editing tool



Develop a model for information exchange that fits the need of your application

Develop a software module that connects each system to the federation. Object Oriented HLA

Connect systems and exchange information. Synchronize time and data

Start up, monitor and troubleshoot simulations, applications, computers and networks.

Record, inspect and play back simulation data exchange. Review and analyze.

Distributed
Training

Distributed
Test & Experimentation



Distributed
Concept Development

Distributed
Analysis



Distributed
Engineering

Distributed Test & Experimentation

FOI





Distributed Analysis



- Signals
- Platform / Weapon
- C2 / Behavior
- SNE
- Effects
- Management


HLA IEEE 1516 Runtime Infrastructure (pRTI™ 1516)



“... advanced, systematic modeling techniques are needed to support engineering of complex, heterogeneous systems. Models provide blueprints for the development and assessment of systems through computer simulation, prior to their deployment.”

J.W. Rozenblit, Arizona Univ.

*The model is the executable
blueprint of tomorrow!*





Purpose: Model and asses a system, including environment, for effectiveness, performance, reliability, etc


- Create an overall design
 - System of Systems
 - Federation of Systems
- Find competencies to create accurate models for all components
- Create models for each component
 - Understanding the real or anticipated behaviors of each system
 - Focus on key aspects, optimal bounding/simplifications, optimal resolution, ...
- Make the models work together (model interoperability)
- Assessments, VV&A and many other challenges...

- » Distributed design
 - » Test and evaluate models from different vendors (Simulation Based Acquisition)
 - » Leverage technical expertise by reusing model components developed by other expert teams
- » Distributed testing of engineering components
 - » Move electrons not people; Connect models of components using distributed simulation infrastructure
 - » Move models not equipment; Perform test and integration events by sharing models before actual hardware/software integration
- » Early integration of engineering components
 - » Interface testing
 - » Function testing
 - » Interoperability testing
 - » Replace models with equipment step-by-step

- » Enable models from different sources (experts, groups, etc) to work together based on open standards
 - » Runtime tools for interoperability, execution planning/monitoring/control, data collection
- » Enable models from widely distributed sites to execute together (between cities or continents)
 - » The "Connected Enterprise"
- » Development tools
 - » Create Information Exchange Data Models between models , generate code, ...
- » And more...



- » The Booster network connects RTI:s and federates into federations.
- » The Booster network connects hosts and Commanders for monitor and control of resources.





- » Technology development is carried out across several NASA centers where different competencies and thus models are available
- » To simulate for example a full launch several models from different centers need to interoperate.
- » Example missions: "Return to the Moon", "Mars Exploration"

- » This short presentation provided an overview of distributed simulation and interoperability
- » Many of these technologies were originally developed in the Aerospace and Defense sector but are now becoming increasingly used in other areas
- » HLA (IEEE 1516) is the leading simulation interoperability standard
 - » Supports any domain and information model
 - » Supports many types of time management
 - » Real-time, frame-based, event-driven, etc
 - » Excellent performance and scalability
 - » Support for widely distributed M&S
- » Major application areas include training, analysis, distributed engineering, test&experimentation and concept development