TDDC17 Robotics/Perception I

Piotr Rudol

IDA/AIICS

LINKÖPING UNIVERSITY

Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance

3

- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder

LINKÖPING UNIVERSITY

Definition of a Robot

- The **word** first appeared in the play RUR published in 1920 by Karel Capek - "robota" meaning "labor"
- A robot is a mechanical device which performs automated physical tasks
- The task can be carried out according to:
 - Direct human supervision (teleoperation)
 - Pre-defined program (industrial robots)
 - Set of general higher-level goals (using AI techniques)

5



TDDC17 Robotics / Perception

Definition of a Robot

Many consider the first robot in the modern sense to be a teleoperated boat, similar to a modern ROV (Remotely Operated Vehicle), devised by Nikola Tesla and demonstrated at an 1898 exhibition in Madison Square Garden. Based on his patent 613,809 for "teleautomation", Tesla hoped to develop the "wireless torpedo" into an automated weapon system for the US Navy.



5

TDDC17 Robotics / Perception

Shakey

Shakey was one of the first autonomous mobile robots, built at the SRI AI Center during 1966-1972. Many techniques present in Shakey's system are still under research today!







http://www.ai.sri.com/shakey

TDDC17 Robotics / Perception

Why do we use robots?

9

10

- The DDD rule:
 - Dangerous, Dirty, and Dull
- Some usage areas:
 - Industrial
 - Military
 - Search and Rescue
 - Space Exploration
 - Research
 - Entertainment
 - ...

TDDC17 Robotics / Perception

Why is (AI) robotics hard?

 Real-life robots have to operate in unknown dynamic environments

- It is a multi-disciplinary domain from mechanics to philosophy...
- It involves many practical problems:
 - it is very technical,
 - it takes a long time from an idea to a built system,
 - debugging can be difficult,
 - expensive.



Categories of robots

- Industrial robots:
 - Mostly stationary
 - Some mobile used for transportation
- Mobile robots:
 - Ground robots legged, wheeled (UGV legged)
 - Aerial rotor-craft fixed-wing (UAV)
 - (Under) water (AUV)
 - Space
- Humanoids:
 - Atlas, Nao, Asimo

11

TDDC17 Robotics / Perception

Categories of robots

Industrial robots:







Categories of robots • Mobile robots: legged





BigDog, 2009

BostonDynamics: https://www.youtube.com/watch?v=3gi6Ohnp9x8

13

TDDC17 Robotics / Perception

Categories of robots • Mobile robots: legged





SpotMini, 2018

BostonDynamics: https://www.youtube.com/watch?v=aFuA50H9uek

Categories of robots • Humanoids





Monty, 2007 Anybots Inc.: https://www.youtube.com/watch?v=23kCn51FW3A

15

TDDC17 Robotics / Perception

Categories of robots • Humanoids





Boston Dynamics

https://www.youtube.com/watch?v=_sBBaNYex3E

15

TDDC17 Robotics / Perception	17
Anatomy of Robots	
Robots consist of:	
Motion mechanism	
 Wheels, belts, legs, propellers 	
Manipulators	
– Arms, grippers	
Computer systems	
 Microcontrollers, embedded computers 	
• Sensors	
17	

TDDC17 Robotics / Perception

Perception

In order for the robots to act in the environment a suite of sensors is necessary:

- Active
 - Emit energy (sound/light) and measure how much of it comes back or/and with how large delay.

- Passive ٠
 - Just observers, measuring energy "emitted" by the environment.



TDDC17 Robotics / Perception

Proprioceptive Sensors

Inform robot about its internal state:

- Shaft encoders
 - Odometry (a measurement of traveled distance)
 - Positions of arm joints
- Inertial sensors
 - Gyroscope (attitude angles: speed of rotation)
 - Accelerometers
- Magnetic
 - Compass
- Force sensors
 - Torque measurement (how hard is the grip, how heavy is the object)

19

TDDC17 Robotics / Perception

Position Sensors

Measure placement of the a robot in its environment.

- Tactile sensors (whiskers, bumpers, etc.)
- Sonar (ultrasonic transducer)
- Laser range finder
- Radar
- (D)-GPS, A-GPS, RTK
- Motion Capture System



Imaging Sensors (Cameras)

Deliver images which can be used by computer vision algorithms to sense different types of stimuli.

- Output data
 - Color
 - Black-White (Thermal)
 - Dynamic Vision Sensor (DVS)
- Configuration
 - Monocular
 - Stereo
 - Omnidirectional
 - Stereo-omnidirectional



Type of sensor (exposure)

- CCD
- CMOS

21

TDDC17 Robotics / Perception

CMOS problem







Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder

TDDC17 Robotics / Perception

Image composition



195	209	221	235	249	251	254	255	250	241	247	248
210	236	249	254	255	254	225	226	212	204	236	211
164	172	180	192	241	251	255	255	255	255	235	190
167	164	171	170	179	189	208	244	254	255	251	234
162	167	166	169	169	170	176	185	196	232	249	254
153	157	160	162	169	170	168	169	171	176	185	218
126	135	143	147	156	157	160	166	167	171	168	170
103	107	118	125	133	145	151	156	158	159	163	164
095	095	097	101	115	124	132	142	117	122	124	161
093	093	093	093	095	099	105	118	125	135	143	119
093	093	093	093	093	093	095	097	101	109	119	132
095	093	093	093	093	093	093	093	093	093	093	119

I(x, y, t) is the intensity at (x, y) at time t



TDDC17 Robotics / Perception Pinhole Camera Model image plane P(X,Y,Z)e pinhole (X,Y) P is a point in the scene, with coordinates (X, Y, Z) P' is its image on the image plane, with coordinates (x, y) x = fX/Z, y = fY/Z - perspective projection by similar triangles. Scale/distance is indeterminate!

25



Lens Distortion

Happens when light passes a lens on its way to the CCD element.



Lens distortion is especially visible for wide angle lenses and close to edges of the image.

LINKÖPING UNIVERSITY

27

TDDC17 Robotics / Perception

Omnidirectional Lens





Camera Calibration

Estimate:

- camera constant f,
- image principle point (optical axis intersects image plane),
- lens distortion coefficients,
- pixel size,

from different views of a calibration object



29

TDDC17 Robotics / Perception

Lens Distortion 2







Why is computer vision hard

- Noise and lighting variations are disturbing images significantly.
- Difficult color perception.
- In pattern recognition objects changing appearance depending on their pose (occlusions).
- Image understanding involves cognitive capabilities (i.e. AI).
- Real-time requirements + huge amount of data.
- ...

31

Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder



TDDC17 Robotics / Perception

Stereo vision

A scene is photographed by two cameras: what do we gain?





CMU CIL Stereo Dataset: Castle sequence





TDDC17 Robotics / Perception

Stereo processing

To determine depth from stereo disparity:

1. Extract the "features" from the left and right images

2. For each feature in the left image, find the corresponding feature in the right image.

- 3. Measure the disparity between the two images of the feature.
- 4. Use the disparity to compute the 3D location of the feature.



37

TDDC17 Robotics / Perception

Stereo Vision for UAVs



Stereo pair of 1m baseline – cross-shaft for stiffness









Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder



Optic Flow

Optical flow methods try to calculate the motion between two image frames which are taken at times t and t + δ t at every pixel position. In practice, it is often done for features instead all of all pixels.





TDDC17 Robotics / Perception Optic flow we all use

46

 Image: State of the state

Optical Mouse as Arduino Web Camera https://www.youtube.com/watch?v=lx6532mrIKA







TDDC17 Robotics / Perception

USC Avatar in Urban Canyon cont'd



53

LINKÖPING UNIVERSITY

53

Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder

Pose Estimation

- It is not always possible to directly measure robots pose in an environment (e.g. no GPS indoor). For a robot to navigate in a reasonable way some sort of position and attitude information is necessary. This is the goal of pose estimation algorithms.
- Example of ARToolkit [Hirokazu Kato et.al.]
- ARToolKit (Plus) video tracking libraries calculate the real camera position and orientation relative to physical markers in real time.





Pose Estimation

TDDC17 Robotics / Perception





Pose Estimation for Indoor Flying Robots

Motivation:

- Indoor-flying robots cannot use GPS signal to measure their position in the environment.
- For controlling a flying robot fast update of readings is required.
- The operation range should be as big as possible in order to be able to fly not just hover.
- Micro-scale robots have very little computation power on board.







The pattern

The cube-shaped structure consists of four faces - only one required for pose estimation

There is a high-intensity LED in each corner; three colors (RGB) code uniquely four patterns. During the flight at least one (at most two) face is visible for the ground robot



TDDC17 Robotics / Perception

Image processing

- Video camera operates with closed shutter for easy and fast diode identification.
- Four identified diodes from one face of the cube go through the "Robust Pose Estimation from a Planar Target" algorithm to extract the pose of the face.



• Knowing which face is visible and the angles of the PTU unit, the complete pose of the UAV relative to the ground robot can be calculated.

Control

- Four PID loops are used to control lateral displacement, yaw and altitude of the UAV
- Control signal (desired attitude + altitude) is sent up to the UAV to be used in the inner loop onboard
- Pan-Tilt unit of the camera mounted on the ground robot is controlled by a simple P controller, which tries to keep the diodes in the center of an image







Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- **Object recognition**
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder





Object recognition

Cascade of boosted classifiers working with Haar-like features





71

TDDC17 Robotics / Perception

Object recognition

stage 1								
a	b	с	d	е	f	g	h	i
F.	i	F.	T.	1 in		res.	(ª	1
					E		音 <i>料</i> :	
stage 2			39		12		22	
a	b	с	d	e	f	g	h	i
de la	5 Pm	F	1.2	No.	1º	880	190-	1.2.
		論願		書簡	-	國編	建設	統
No. or and a second s	k	1	m	n	O COLOR	City City	BEAUTION	
	T _{it}		4	4				
5		12	a _1					





x4

Human body detection with UAVs



75

TDDC17 Robotics / Perception

Human body detection with UAVs







Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder

79

80

TDDC17 Robotics / Perception

Structured Light





















Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder

95

96

TDDC17 Robotics / Perception











 Yamaha RMAX
 DJI Matrice 600 Pro

 Sick LMS 291
 Velodyne Puck









Outline

- Introduction
- Camera model & Image formation
- Stereo-vision
 - Example for UAV obstacle avoidance
- Optic flow
- Vision-based pose estimation
 - Example for indoor UAVs
- Object recognition
 - Example for outdoor UAVs
- Kinect: Structured Light
- Laser Range Finder
- <u>Next lecture: Localisation, planning, other</u> <u>hardware...</u>

