

# Neural architectures for dependency parsing

Marco Kuhlmann

Department of Computer and Information Science

# Learning problems in dependency parsing

- Learning a greedy transition-based dependency parser amounts to learning the transition classifier.

[Chen and Manning \(2014\)](#), [Kiperwasser and Goldberg \(2016\)](#)


- Learning an arc-factored graph-based dependency parser amounts to learning the arc scores.

[Kiperwasser and Goldberg \(2016\)](#), [Dozat and Manning \(2017\)](#)

# Chen and Manning (2014)



- Pre-neural transition classifiers relied on linear models with hand-crafted combination features.
- C&M propose to replace the linear model with a two-layer feedforward network (FNN).
- The standard choice for the transfer function is the rectified linear unit (ReLU).

C&M use the cube function,  $f(x) = x^3$ .




feedforward  
neural network

I wanted to try someplace new



I wanted to try someplace new



# Features

- C&M embed the top 3 words on the stack and buffer, as well as certain descendants of the top words on the stack.

word embedding dimension = 50

- In addition to word embeddings, they also use embeddings for part-of-speech tags and dependency labels.

tag embedding dimension = label embedding dimension = 50

- The resulting input dimension of the FNN is 2400.

# Training

- To train their parser, C&M minimise the standard cross-entropy loss, plus an L2 regularisation term.
- To generate training examples for the transition classifier, they use the static oracle for the arc-standard algorithm.

can be generated off-line

# Parsing accuracy



	UAS	LAS
Baseline, transition-based	89.4	87.3
Baseline, graph-based	90.7	87.6
Chen and Manning (2014)	<b>91.8</b>	<b>89.6</b>
<u>Weiss et al. (2015)</u>	93.2	91.2

Parsing accuracy on the test set of the Penn Treebank + conversion to Stanford dependencies




## Kiperwasser and Goldberg (2016)

- The neural parser of C&M learns useful feature combinations, but the need to carefully design the core features remains.
- K&G propose to use a minimal set of core features based on contextualised embeddings obtained from a Bi-LSTM.  
*Bi-LSTM is trained with the rest of the parser.*
- They show that this approach gives state-of-the-art accuracy both for transition-based and for graph-based parsing.



I wanted to try someplace new







## Features and training (transition-based parser)

- For their transition-based parser, K&G embed the top 3 words on the stack, as well as the first word in the buffer.

word embedding dimension = 100, tag embedding dimension = 25

- In contrast to C&M, they use a dynamic oracle, so they cannot generate training examples in an off-line fashion.





## Features and training (graph-based parser)

- For their graph-based parser, K&G embed the head and dependent of each arc.

word embedding dimension = 100, tag embedding dimension = 25

- The training objective is to maximise the margin between the score of the gold tree  $y^*$  and the highest-scoring incorrect tree  $y$ :

$$L(\theta) = \max(0, 1 + \max_{y \neq y^*} \text{score}(x, y) - \text{score}(x, y^*))$$

# Parsing accuracy

	UAS	LAS
Chen and Manning (2014)	91.8	89.6
Weiss et al. (2015)	93.2	91.2
K & G (2016), graph-based	93.0	90.9
K & G (2016), transition-based	<b>93.6</b>	<b>91.5</b>

Parsing accuracy on the test set of the Penn Treebank + conversion to Stanford dependencies





## Dozat and Manning (2017)

- Based on the context-dependent embeddings, two FNNs create specialised representations of each word as a head/dependent:

$$\mathbf{h}_i = \text{FNN}_h(\mathbf{v}_i) \quad \mathbf{d}_i = \text{FNN}_d(\mathbf{v}_i)$$

- These specialised representations are then scored via a bilinear layer with weight tensor  $\mathbf{U}$  and bias vector  $\mathbf{b}$ :

$$\text{score}(x, i \rightarrow j) = \mathbf{h}_i \mathbf{U} \mathbf{d}_j^\top + (\mathbf{h}_i \mathbf{b})^\top$$



# Parsing accuracy

	UAS	LAS
Chen and Manning (2014)	91.8	89.6
K & G (2016), graph-based	93.0	90.9
K & G (2016), transition-based	93.6	91.5
Dozat and Manning (2017)	<b>95.7</b>	<b>94.1</b>

Parsing accuracy on the test set of the Penn Treebank + conversion to Stanford dependencies