Software verification Spring 2021

Homework 2

Ahmed Rezine

Propose a NuSmv model for a traffic light controller managing the intersection of two heavily trafficed bike-roads: a north-south road and an east-west road.

Each road has a single direction. The system has two sensors (captured with two boolean variables north_sensor and east_sensor) that sense the arrival of bikes (respectively from the north and biking south or from the east and biking west). It has also two red lights modeled as two boolean variables north_light and east_light, each capturing if the corresponding light is green or red. The north_sensor and east_sensor variables are updated with non-deterministic values in the main module (to capture random arrival of bikes). Additional boolean variable north_req (resp. east_req) is used by the north-south controller (resp. east-west controller) to remember that some bikes were sensed on the north-south (resp. east-west) road but did not get the green light yet.

Your solution should consist of two modules. A main module and a controller module. The controller module will be instantiated twice: once for the north-south controller and another for the east-west controller. The north-south and east-west instantiations communicate via two boolean variables north_lock and east_lock.

The main module initializes the lock and light variables, instantiates the two controllers and updates (non-deterministically) the arrival of the bikes (via the sensor variables).

The north-south controller (the east-west controller is similar) has a number of states (e.g., idle, wait, critical, more?). It updates its state and the values of the north_req, north_light and north_lock variables based on their current values and on the value of the east_lock and north_sensor values.

Express in CTL the following properties:

- The lights never get simultaneously green on both sides (mutual exclusion).
- Each time a bike is sensed on the north-south road (respectively, east-west road), the corresponding light gets eventually green (liveness).
- If bikes stop coming on the north-south road (resp. east-west road), then lights eventually become red and stay that way (hence a periodic solution will not fit).

Propose a "reasonable" solution that satisfies (as in model-check with NuSMV) the above properties. You will need suitable fairness conditions for the last two pairs of properties. Your solution should consist of a readable and well documented nusmy file. Your are welcome to add more variables or states. This source might be relevant https://www.cs.cmu.edu/~mtschant/15414-f07/lectures/traffic.pdf. State any other sources that might have inspired you.

OPTIONAL: Describe (in an accompagning text document) reasonable requirements for two pedestrian controllers and the corresponding changes to your solution (you do not have to model check it).