

An Approach for Repairing Incoherent Ontologies

Ying Li¹ and Patrick Lambrix^{1,2,3}

¹ Department of Computer and Information Science, Linköping University, Sweden

² The Swedish e-Science Research Centre, Linköping University, Sweden

³ Department of Building Engineering, Energy Systems and Sustainability Science,
University of Gävle, Sweden

`firstname.lastname@liu.se`

Abstract. The quality of ontologies and their alignments is crucial for developing high-quality ontology-based applications. In this paper we propose an approach for repairing incoherent ontologies and ontology networks that is based on axiom weakening and completion.¹

1 Introduction

As ontologies become more prevalent and are used extensively in many different domains, the quality of ontologies and ontology networks, i.e., a set of ontologies connected through alignments, has become a key factor for supporting semantically-enabled applications. Therefore, ontologies with defects need to be repaired. One kind of defect that often occurs is the fact that the ontology or ontology network is incoherent, i.e., it contains unsatisfiable concepts. After a detection phase that finds the unsatisfiable concepts, a common method for repairing is to find justifications for the unsatisfiability and remove axioms in these justifications. For an overview of methods and examples, we refer to [6]. However, most approaches suffer the following issues. First, they are purely logic-based and therefore may remove correct axioms (e.g., [8]). Therefore, in the formalization of the repairing problem in [6] it is suggested that an oracle (e.g., a domain expert) is involved in validating logical solutions. Furthermore, removing an axiom may remove more knowledge than necessary. Sometimes it may be enough to replace an axiom with a weakened version of the axiom (e.g., [9,1]). Further, weakening axioms may also be seen as removing the axiom and then adding the weakened axiom. When adding axioms we can perform completion as defined in [6] to add more correct knowledge than just the axiom.

In this paper we propose an approach for repairing incoherent ontologies that deals with these issues using axiom weakening and completion. The approach also uses an oracle in different validation steps. Furthermore, the approach can directly be applied to ontology networks by considering the mappings in the ontologies as axioms and thus considering the ontology network as one ontology.

¹ Copyright © 2021 for this paper by its authors. Use permitted under Creative Commons License Attribution 4.0 International (CC BY 4.0).

In this case repairing the ontology may remove or weaken both axioms in the ontologies or in the mappings. We can also define a variant of the approach that deals with mapping repair, as most current approaches assume the knowledge in the ontologies is correct and only mappings may be removed or weakened.

2 Repairing incoherence

In this paper we deal with the taxonomic part of the ontology, i.e., subsumption axioms between named concepts in the ontology. Equivalence axioms are treated as two subsumption axioms. We assume that we have a set of axioms W that when removed from the ontology lead to a coherent ontology. This set could be obtained by using a traditional approach for ontology debugging together with domain expert validation of the proposed solutions. Instead of just removing these axioms our approach will try to keep more knowledge in the ontology.

Algorithm 1 Repairing Algorithm

Input: An incoherent ontology \mathcal{O} , a set of unwanted axioms W
Output: A coherent ontology \mathcal{O}_r that repairs \mathcal{O}

- 1: $\mathcal{O}_r \leftarrow \mathcal{O}$
- 2: **for each** $\alpha \sqsubseteq \beta \in W$ **do**
- 3: $\mathcal{O}_r \leftarrow \mathcal{O}_r \setminus \{\alpha \sqsubseteq \beta\}$
- 4: $wsup \leftarrow \{ sp \in sup(\beta) \mid \mathcal{O}_r \not\models \alpha \sqsubseteq sp \wedge Or(\alpha \sqsubseteq sp) = \text{True} \wedge \neg \exists sp' \in sup(\beta):$
 $(Or(\alpha \sqsubseteq sp') = \text{True} \wedge sp' \sqsubset sp) \}$
- 5: $R_w \leftarrow \emptyset$
- 6: **for each** $sp \in wsup$ **do**
- 7: $Source \leftarrow sup(\alpha) - sup(sp), Target \leftarrow (sub(sp) - sub(\beta)) - sub(\alpha)$
- 8: $WR \leftarrow \{ \alpha_w \sqsubseteq \beta_w \mid \alpha_w \in Source \wedge \beta_w \in Target \wedge Or(\alpha_w \sqsubseteq \beta_w) = \text{True}$
 $\wedge \neg \exists \alpha'_w \sqsubseteq \beta'_w: (Or(\alpha'_w \sqsubseteq \beta'_w) = \text{True} \wedge (\alpha_w \sqsubset \alpha'_w \vee \beta'_w \sqsubset \beta_w)) \}$
- 9: $R_w \leftarrow R_w \cup WR$
- 10: **end for**
- 11: $\mathcal{O}_r \leftarrow \mathcal{O}_r \cup R_w$
- 12: **end for**

Given an incoherent ontology \mathcal{O} , Algorithm 1 describes the general process of repairing. In the algorithm we denote with $sup(A)$ the set of all the super-concepts of a concept A and with $sub(A)$ the set of all the sub-concepts of A . Further, the oracle Or represents the domain expert and assigns a truth value True or False to an axiom. For every unwanted axiom $\alpha \sqsubseteq \beta$ we remove it from the ontology (line 3) and try to weaken it by finding axioms of the form $\alpha \sqsubseteq sp$ with sp a super-concept of β , that are correct according to the domain expert and retain the most knowledge. The set $wsup$ collects concepts sp that satisfy these requirements (line 4).

Further, we try to find improved axioms for a weakened axiom and collect these in the set WR . We try to improve a weakened axiom by finding an $\alpha_w \sqsubseteq \beta_w$ that is correct according to the domain expert and such that $\alpha \sqsubseteq \alpha_w$ and $\beta_w \sqsubseteq \beta$. We call this completing as in [6]. In that case we know that $\alpha \sqsubseteq \beta$ can be derived from these axioms. The $Source$ set collects the candidates for α_w . It

mappings and axioms in the ontologies. In this case Algorithm 1 can be used as is. In many current approaches for alignment repair, however, only mappings are removed. In this case we can use a variant of Algorithm 1 (variant 2) that distinguishes between axioms and mappings, and only mappings are removed and weakened.

We used the ontologies MA and NCI-A from the OAEI Anatomy track [2] and alignments from 2018 generated by AML without its repair module (denoted as AML-Map) [3] and LogMapLite [5]. For each alignment together with MA and NCI-A an incoherent network was produced and repaired. We used OntoDebug in Protégé to generate maximum 9 repairs (default setting) that we could use as W in Algorithm 1. We removed the repairs with disjointness axioms. As we did not have a domain expert, we used the remaining repairs for W . For AML-Map this gave us 1 repair with only mappings (which can be used in variants 1 and 2) and 8 repairs where both axioms and mappings are used (which can only be used in variant 1). The number of axioms and mappings in a repair ranged from 1 to 4. For LogMapLite there were 3 repairs with axioms and mappings, but none with only mappings. The number of axioms and mappings in a repair was always 2. For each of the repairs generated in this session each axiom and each mapping led to 1 weakened axiom or mapping each. This means that for each suggested repair by OntoDebug it was possible to find a way to keep more knowledge in the ontology than when the axioms and mappings in the repair were removed (depending on the validation of the domain expert). Furthermore, for this example the source sets of the weakened axioms were always singletons, but the sizes of the target sets ranged from several hundreds to over 3000 elements. Thus, depending on the validation of the domain expert, more knowledge could be added to the ontology. In future work we will investigate deeper into more possible repairs and have domain experts validate the axioms and mappings in each step of the approach.

4 Conclusion and Future work

In this paper, we proposed an approach for repairing incoherent ontologies which focuses on preserving as much knowledge as possible. It combines a debugging approach, an axiom weakening approach and a completion approach together with domain expert validation. We intend to integrate the approach within the RepOSE system [7,4]. Furthermore, we will investigate the influence of other logical constructs in ontology representation languages and use our approach on ontologies that we are developing in other domains.

Acknowledgements. This work has been financially supported by the Swedish e-Science Research Centre (SeRC), the Swedish Research Council (Vetenskapsrådet, dnr 2018-04147), and the Swedish Agency for Economic and Regional Growth (Tillväxtverket).

References

1. Baader, F., Kriegel, F., Nuradiansyah, A., Peñaloza, R.: Making repairs in description logics more gentle. In: KR. pp. 319–328 (2018)
2. Dragisic, Z., Ivanova, V., Li, H., Lambrix, P.: Experiences from the anatomy track in the ontology alignment evaluation initiative. *J Biomed Semant* **8**(1) (2017)
3. Faria, D., Pesquita, C., Santos, E., Palmonari, M., Cruz, I.F., Couto, F.M.: The agreementmakerlight ontology matching system. In: OTM. pp. 527–541 (2013)
4. Ivanova, V., Lambrix, P.: A unified approach for aligning taxonomies and debugging taxonomies and their alignments. In: ESWC. pp. 1–15 (2013)
5. Jiménez-Ruiz, E., Grau, B.C., Cross, V.: Logmap family participation in the OAEI 2017. In: *Ontology Matching Workshop*. vol. 2032, pp. 153–157 (2017)
6. Lambrix, P.: Completing and debugging ontologies: state of the art and challenges (2020), arXiv:1908.03171
7. Lambrix, P., Ivanova, V.: A unified approach for debugging is-a structure and mappings in networked taxonomies. *J Biomed Semant* **4**, 10 (2013)
8. Pesquita, C., Faria, D., Santos, E., Couto, F.M.: To repair or not to repair: reconciling correctness and coherence in ontology reference alignments. In: *Ontology Matching Workshop*. pp. 13–24 (2013)
9. Troquard, N., Confalonieri, R., Galliani, P., Peñaloza, R., Porello, D., Kutz, O.: Repairing ontologies via axiom weakening. In: AAIL. pp. 1981–1988 (2018)